

84

Retracement and Resurvey of Willamette Meridian.

CHAINS

firmly set, marked and witnessed as described by the Surveyor General.

Thence N.0*14'E.

Desc. 160 ft. on N. slope.

6.10 Creek, 2 lks. wide, course W., asc. 185 ft. on S. slope.

16.80 Spur, slopes SW., descend 280 ft. on NW. slope.

29.75 Spur, slopes NW. desc. 175 ft. on NE. slope, to

36.32 Point of intersection with line bet. secs. 6 and 7, determined as hereinafter set forth.

Set a conglomerate stone, 22x12x8 ins., 16 ins. in the ground, for closing cor. of secs. 6 and 7, marked CC on E., with 1 groove on N., and 5 grooves on S. face, from which

A pine, 48 ins. diam., bears N.77*E., 139 lks. dist., marked T 29 S R 1 E S 6 C C B T.

A fir, 30 ins. diam., bears S.53*E., 135 lks. dist., marked T 29 S R 1 E S 7 C C B T.

No iron post available for this corner.

Land, mountainous.

Soil, clay loam, 2nd. rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, chinquapin, laurel, hazel and vine maple.

N.0*14'E., resurveying W. Bdy. of sec. 6.

Over mountainous land, through heavy timber and dense Undergrowth.

Desc. 190 ft. on N. slope, to

3.66 Intersect the $\frac{1}{2}$ sec. cor. on E. Bdy. of sec. 12, T. 29 S.,

R. 1 W., which is a basalt stone, 4x10x6, ins. above ground, firmly set, marked and witnessed as described by the Surveyor General, except that the bearing tree, E. of line is dead and fallen. I take new bearing tree.