

85

Retracement and Resurvey of Willamette Meridian.

CHAINS	
	From the corner.
	(Old bearing tree) A fir, 14 ins. diam., bears S.84*W., 19 lks. dist., marked $\frac{1}{4}$ S 12 B T.
	(New bearing tree) A hemlock, 6 ins. diam., bears N.60*W., 14 lks. dist., marked $\frac{1}{4}$ S 12 B T.
	Thence N.0*12'E.
	Desc. 90 ft. on N. slope.
2.10	Creek, 5 lks. wide, course NW., asc. 80 ft. on S. slope.
5.15	Small spur, slopes SW., desc. 20 ft. on NW. slope.
12.10	Ravine, course SW., asc. 700 ft. on S. slope.
35.60	Spur, slopes NW.
36.34	Point 40.00 chs. N. of closing cor. of secs. 6 and 7.
	Set a granite stone, 20x12x12 ins. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 6 only, marked $\frac{1}{4}$ on E. face, from which
	A fir. 18 ins. diam., bears N.35*E., 53 lks. dist., marked $\frac{1}{4}$ S 6 B T.
	A fir, 20 ins. diam., bears S.30*E., 22 lks. dist., marked $\frac{1}{4}$ S 6 B T.
	No iron post available for this corner.
	Desc. 20 ft. on NE. slope, to
40.03	Intersect the cor. of secs. 1 and 12, T 29 S., R. 1 W., which is a basalt stone, 5x12x10 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General.
	Thence N.0*16'E.
	Desc. 530 ft. on NE. slope.
14.80	Creek, 5 lks. wide, course NW., asc. 410 ft. on SW. slope.
35.60	Spur, slope NW.
36.25	Point of intersection with N. Bdy. of the Tp., determined as hereinafter set forth.