

86

Retracement and Resurvey of Willamette Meridian.

CHAINS

Set a basalt stone, 24x12x8 ins. 18 ins. in the ground, for closing cor. of Tps. 28 and 29 S., R. 1 E., marked CC on W., with 6 grooves on N, E and S. faces, from which

A fir, 18 ins. diam., bears N.32°E., 33 lks. dist., marked T 28 S R 1 E S 31 C C B T.

A fir, 30 ins. diam., bears S.63°E., 16 lks. dist., marked T 29 S R 1 E S 6 C C B T.

No iron post available for this corner.

The $\frac{1}{4}$ sec. cor. on E. Bdy. of sec. 1, T. 29 S., R. 1 W., which is a basalt stone, 5x10x6 ins. above ground, firmly set, marked and witnessed as described by the Surveyor General, bears N.0°16'E., 3.73 chs. dist. I obliterate marks on bearing tree E. of line, and take new bearing tree.

From the corner,

(New bearing tree) A fir, 7 ins. diam., bears S.71°W., 36 lks. dist., marked $\frac{1}{4}$ S 1 B T.

(Old bearing tree) A pine, 24 ins. diam., bears N.42°W., 40 lks. dist., marked $\frac{1}{4}$ S 1 B T.

Land, mountainous.

Soil, clay loam. stony in places, 2nd. and 3rd. rate.

Timber, fir, hemlock, cedar and pine.

Undergrowth, chinquapin, laurel, hazel and vine maple.

Retracement and Resurvey of S. Bdy. T. 28 S. R. 1 W.,
Retracement of Portion of Willamette Meridian, T. 29 S.,
Survey of Portion of N. and W. Boundaries of,
Township 29 South, Range 1 West.
Retracement and Resurvey of Portion of Subdivisions,
Township 29 South, Range 1 West.
Survey of Subdivisions of Sections 1 to 12 Inclusive,
Township 29 South, Range 1 West.
Of the Willamette Meridian,
Executed by, Fred Mensch, U. S. Cadastral Engineer,
Under Special Instructions dated, June 7, 1922.

Retracements.

From the cor. of Tps. 28 and 29 S., R. 1 W., East, retracing the S. Bdy. of sec. 31., at 37.29 chs. fall 7 lks. N.