

87

Resurvey of S. Bdy., T. 28 S., R. 1 W.

CHAINS

Retracements.

of the $\frac{1}{4}$ sec. cor., and, at 77.55 chs. fall 11 lks. N. of the cor. of secs. 5, 6, 31, and 32.

East, retracing the S. Bdy. of sec. 32, at 40.31 chs. intersect the $\frac{1}{4}$ sec. cor., and, at 80.49 chs. intersect the cor. of secs. 4, 5, 32 and 33.

East, retracing the S. Bdy. of sec. 33, at 40.29 chs. intersect the $\frac{1}{4}$ sec. cor., and, at 80.46 chs. fall 23 lks. N. of the cor. of secs. 3, 4, 33 and 34.

East, retracing the S. Bdy. of sec. 34, at 40.58 chs. fall 21 lks. N. of the $\frac{1}{4}$ sec. cor., and, at 80.74 chs. fall 21 lks. N. of the cor. of secs. 2, 3, 34 and 35.

East, retracing the S. Bdy. of sec. 35, at 40.24 chs. intersect the $\frac{1}{4}$ sec. cor., and, at 80.72 chs. fall 24 lks. N. of the cor. of secs. 1, 2, 35 and 36.

East, retracing the S. Bdy. of sec. 36, at 39.57 chs. intersect the $\frac{1}{4}$ sec. cor., and, at 79.92 chs. fall 18 lks. N. of the cor. of Tps. 28 and 29 S., R. 1 W.

I commence at the cor. of Tps. 28 and 29 S., R. 1 W., on the E. Bdy. of T. 28 S., R. 2 W., which is a basalt stone, 5x12x7 ins. above ground, firmly set, marked with 6 notches on N, E, and S. edges, from which

A fir, 20 ins. diam., bears N.60°E., 55 lks. dist., marked T 28 S R 1 W S 31 B T. (old B T.)

A fir, 28 ins. diam., bears S.70°E., 50 lks. dist., marked T 29 S R 1 W S 6 B T. (Old B T.)

and run

S.89°54'E., along the S. Bdy. of sec. 31.

Desc. E. slope, 68 ft. through heavy timber and dense undergrowth.

2.34 Creek, 5 lks. wide, course SE., asc. 36 ft.

4.50 Top of small spur, slopes SE., desc. 113 ft. to gulch.

6.48 Point for $\frac{1}{4}$ sec. cor. of sec. 6, later determined.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., of sec. 6 only, with brass cap marked

$\frac{1}{4}$ S 6
1922

From which