

## Resurvey of S. Bdy. T. 28 S., R. 1 W.

## CHAINS

A hemlock, 14 ins. diam., bears S.72\*E., 24 lks. dist., marked  $\frac{1}{4}$  S 6 B T.

A fir, 14 ins. diam., bears S.78\*W., 29 lks. dist., marked  $\frac{1}{4}$  S 6 B T.

11.28 Gulch, course S., asc. SW. slope, 394 ft. to

37.29 Intersect the old  $\frac{1}{4}$  sec. cor., which is a basalt stone, 5x12x7 ins. above ground, firmly set, marked  $\frac{1}{4}$  on N. face, and witnessed as described by the Surveyor General. I obliterate the marks on the old SW. bearing tree and change this cor. to refer to sec. 31 only, and mark a new bearing tree as follows:

A cedar, 18 ins. diam., bears N.33\*E., 55 lks. dist., marked  $\frac{1}{4}$  S 31 B T. (New B T.)

A fir, 18 ins. diam., bears N.45\*W., 46 lks. dist., marked  $\frac{1}{4}$  S 31 B T. (Old B T.)

Thence

S.89\*57'E., continuing my measurements.

Continue asc. 82 ft.

41.09 Top of asc., desc. 41 ft.

46.48 Bottom of desc., point for closing cor. of secs. 5 and 6, hereinafter described, asc. 61 ft.

48.74 Top of asc. on S. slope, desc. 90 ft. to

59.65 Spring branch, 2 lks. wide, course S., asc. SW. slope, 247 ft. to

77.55 Intersect the old cor. of secs. 5, 6, 31 and 32, which is a basalt stone, 5x14x6 ins. above ground, firmly set, marked with 5 notches on E. and 1 notch on W. edge, and witnessed as described by the surveyor general. I change this cor. to refer to secs. 31 and 32 only, and obliterate the marks on the old SE. and SW. bearing trees. The cor. is now witnessed as follows:

A fir, 16 ins. diam., bears N.75\*E., 15 lks. dist., marked T 28 S R 1 W S 32 B T. (Old B T.)