

89

Resurvey of the S. Bdy. T. 28 S., R. 1 W.

CHAINS

A fir, 14 ins. diam., bears N.30*W., 24 lks. dist., marked T 28 S R. 1 W. S 31 B T. (Old B T.) The bearing of this tree was erroneously reported N.80*W.
Land, mountainous.

Soil, rocky clay loam, 4th. rate.

Timber, fir, hemlock, sugar pine, live oak and laurel.

Undergrowth, tan oak, vine maple, salal and rhododendron.

East, along the S. Bdy. of sec. 32.

Asc. SW. slope, 324 ft. to ridge, through heavy timber and dense undergrowth.

8.99 Point for $\frac{1}{4}$ sec. cor. of sec. 5, later determined.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 5 only, with brass cap marked

$\frac{1}{4}$ S 5
1922

from which

A fir, 48 ins. diam., bears S.47*E., 39 lks. dist., marked $\frac{1}{4}$ S 5 B T.

A laurel, 10 ins. diam., bears S.60*W., 26 lks. dist., marked $\frac{1}{4}$ S 5 B T.

19.45 Top of ridge, bears NW. and SE., asc. gradually 85 ft. along N. slope.

36.30 Top of asc. on N. slope, desc. 35 ft.

40.31 Intersect the old $\frac{1}{4}$ sec. cor., which is a basalt stone, 5x12x10 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, and witnessed as described by the surveyor General. I change this cor. to refer to sec. 32 only, obliterated the marks on the old SW. bearing tree and mark a new tree as follows: