

Resurvey of the S. Bdy. T. 28 S., R. 1 W.,

CHAINS

and SW. bearing trees and mark a new bearing tree as follows:

A fir, 26 ins. diam., bears N.72°E., 21 lks. dist., marked T 28 S R 1 W S 34 B T. (Old B T.)

A chinquapin, 9 ins. diam., bears N.64°W., 35 lks. dist., marked T 28 S R 1 W S 33 B T. (New B T.)

Land, mountainous.

Soil, rocky clay loam, 4th. rate.

Timber, fir, hemlock, chinquapin, cedar and pine.

Undergrowth, salal, vine maple, chinquapin and rhododendron.

S.89°42'E., along the S. Bdy. of sec. 34.

Asc. W. slope, 393 ft. through heavy timber and dense undergrowth.

8.15 Point for $\frac{1}{4}$ sec. cor. of sec. 3, later determined.

Set an iron post, 3 ft. long 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 3 only, with brass cap marked

$\frac{1}{4}$ S 3
1922

from which

A cedar, 30 ins. diam., bears S.43°E., 25 lks. dist., marked $\frac{1}{4}$ S 3 B T.

A fir, 28 ins. diam., bears S.43°W., 7 lks. dist., marked $\frac{1}{4}$ S 3 B T.

21.35 of Top/asc, descend gradually along S. slope, 50 ft.

29.45 Dry gulch, course SW., asc. abrupt W. slope 410 Ft.

40.58 Intersect the old $\frac{1}{4}$ sec. cor., which is a basalt stone, 5x10x6 ins. above ground, firmly set, marked $\frac{1}{4}$ on N. face, and witnessed as described by the Surveyor General. I obliterate marks on the old SE. bearing tree, change this cor. to refer to sec. 34 only, and mark a