

## Resurvey of the S. Bdy. T. 28 S., R. 1 W.,

CHAINS

 $\frac{1}{4}$  S 1  
1922

from which

A fir, 18 ins. diam., bears S.36\*E., 52 lks. dist.,  
marked  $\frac{1}{4}$  S 1 B T.

A fir, 12 ins. diam., bears S.25\*W., 6 lks. dist.,  
marked  $\frac{1}{4}$  S 1 B T.

28.10 Creek, 3 lks. wide, course SE., asc. SW. slope, 232 ft.

39.57 Intersect the old  $\frac{1}{4}$  sec. cor., which is a basalt stone,  
4x12x5 ins. above ground, firmly set, marked  $\frac{1}{4}$  on N.  
face, and witnessed as described by the surveyor  
general. I obliterate marks on the old SE. bearing tree,  
change this cor. to refer to sec. 36 only, and mark a  
bearing tree as follows:

A chinquapin, 8 ins. diam., bears N.13\*E., 65 lks.  
dist., marked  $\frac{1}{4}$  S 36 B T. (New B T.)

A fir, 36 ins. diam., bears N.50\*W., 6 lks. dist.,  
marked  $\frac{1}{4}$  S 36 B T. (Old B T.)

Thence

S.89\*45'E., continuing my measurements.

Continue asc. of SW. slope, 52 ft.

41.60 Top of spur, slopes S., desc. abrupt SE. slope, 456 ft.

59.10 Boulder creek, 40 lks. wide, course SW., asc. gradually  
over creek bottoms, 159 ft.

79.92 Intersect the cor. of Tps. 28 and 29 S., R. 1 W., on the  
W. Bdy. of T. 28 S., R. 1 E., which is a basalt stone,  
5x12x10 ins. above ground, firmly set, marked with 6  
notches on N, S, and W. edges, and witnessed by:

A fir, 30 ins. diam., bears S.46\*W., 69 lks. dist.,  
marked T 29 S R 1 W S 1 B T. (Old B T.)

A fir, 36 ins. diam., bears N.75\*W., 27 lks. dist.,  
marked T 28 S R 1 W S 36 B T. (Old B T.)

Land, mountainous.