

101

Subdivisions, T. 29 S., R. 1 W.

CHAINS

40.72 Intersect the old $\frac{1}{4}$ sec. cor. which is a porphyry stone, 12x8x6 ins., firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 18 only, obliterate marks on the NE. bearing tree, and reset the stone, 8 ins in the ground, marked $\frac{1}{4}$ S 18 on S. face, from which

A red fir, 20 ins. diam., bears S.69*E., 34 lks. dist., marked $\frac{1}{4}$ S 18 B T. (Old B T.)

A chinquapin, 6 ins. diam., bears S.9*W., 43 lks. dist., marked $\frac{1}{4}$ S 18 B T. (New B T.)

Thence East, continuing my measurements. Desc. SE. slope, 378 ft. to sec. cor.

69.20 Spring branch, 2 lks. wide, course SE. thence along S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 7 and 8, with brass cap marked

T29S	R1W
S7	S8
S18	
1922	

from which

A yellow pine, 24 ins. diam., bears N.75*E., 19 lks. dist., marked T 29 S R 1 W S 8 B T.

A yellow pine, 24 ins. diam., bears N.66*W., 5 lks. dist., marked T 29 S R 1 W S 7 B T.

81.05 Intersect the old cor. of secs. 7, 8, 17 and 18, which is a chinquapin, 10 ins. diam., marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 17 and 18 only, obliterate marks on the NE. and NW. bearing trees and on the NE. and NW. sides of the cor. tree and remark the cor., R.1 W S 17 on SE., and T 29 S S 18 on SW. sides., from which