

County Surveyor's Record, Douglas County, Oregon

103

Subdivisions, T. 29 S., R. 1 W.

CHAINS

marked $\frac{1}{4}$ S 17 on S. face, from which

A fir, 6 ins. diam., bears S.43*E., 21 lks. dist.,
marked $\frac{1}{4}$ S 17 B T. (New B T.)

A fir, 20 ins. diam., bears S.57*W., 20 lks. dist.,
marked $\frac{1}{4}$ S 17 B T. (Old B T.)

Thence

East, continuing my measurements.

Continue desc. of SE. slope, 417 ft. to sec. cor.

78.96 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 8 and 9, with brass cap
marked

| | |
|------|-----|
| T29S | R1W |
| S8 | S9 |
| S17 | |
| 1922 | |

from which

A yew, 7 ins. diam., bears N.13*E., 28 lks. dist.,
marked T 29 S R 1 W S 9 B T.

A cedar, 18 ins. diam., bears N.47*W., 28 lks. dist.,
marked T 29 S R 1 W S 8 B T.

80.54 Intersect the old cor. of secs. 8, 9, 16 and 17, which
is an ironstone, 5x10x8 ins. above ground, firmly set,
marked with 4 notches on S. and E. edges, and witnessed
as described by the surveyor general. I obliterate marks
on the NE. and NW. bearing trees, mark 2 notches on W.
edge of stone and change this cor. to refer to secs.
16 and 17 only, from which

A hemlock, 16 ins. diam., bears S.17*E., 45 lks.
dist. marked T 29 S R 1 W S 16 B T. (Old B T.)

A hemlock, 12 ins. diam., bears S. 54*W., 35 lks.
dist., marked T 29 S R 1 W S 17 B T. (Old B T.)

Land, mountainous.

Soil, rocky clay loam, 3rd. rate.