

Subdivisions, T. 29 S., R. 1 W.

CHAINS	
	Timber, cedar, fir, hemlock, yew and chinquapin. Undergrowth, salal, rhododendron and vine maple.
	S.89*41'E., along the N. Bdy. of sec. 16. Desc. gradually through heavy timber and dense undergrowth.
0.57	Spring branch, 3 lks. wide, course NE., asc. NW. slope, 144 ft.
8.16	Top of ridge, bears NE. and SW., desc. SE. slope, 115 ft.
15.64	Spring branch, 2 lks. wide, course NE., asc. 56 ft.
17.15	Top of asc, descend 73 ft. to
25.40	Draw, course NE., asc. gradually 41 ft.
28.00	Enter burn, bears N. and S.
34.00	Top of asc. descend 161 ft. to $\frac{1}{4}$ sec. cor.
38.42	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 9 only, with brass cap marked
	$\frac{1}{4}$ S 9 1922
	from which
	A fir, 14 ins. diam., bears N.14*E., 203 lks. dist., marked $\frac{1}{4}$ S 9 B T.
	A madrona, 14 ins. diam., bears N.37*W., 165 lks. dist., marked $\frac{1}{4}$ S 9 B T.
40.63	Intersect the old $\frac{1}{4}$ sec. cor., which is a basalt stone, 4x10x6 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, except the old bearing trees have been killed by fire. I change this cor. to refer to sec. 16 only; reset the stone, 8 ins. in the ground, marked $\frac{1}{4}$ S 16 on S. face, from which
	A sugar pine, 16 ins. diam., bears S.12*E., 196 lks. dist., marked $\frac{1}{4}$ S 16 B T.