

105

Subdivisions, T. 29 S., R. 1 W.

CHAINS

A fir, 18 ins. diam., bears S.9*W., 178 lks. dist.,
marked $\frac{1}{4}$ S 16 B T.

I obliterate marks on the old NE. bearing tree.

Thence

S.89*45'E., continuing my measurements.

Desc. general NE. slope, 544 ft. to sec. cor.

45.20 Trail, bears N. and S.

46.65 Leave burn, bears N. and S.

50.10 Spring branch, 2 lks. wide, course NE.

54.65 Enter burn, bears N. and S.

78.42 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for cor. of secs. 9 and 10, with brass cap
marked

T29S	R1W
S9	S10
S16	
1922	

from which

A fir, 12 ins. diam., bears N.40*E., 27 lks. dist.,
marked T 29 S R 1 W S 10 B T.

A fir, 18 ins. diam., bears N.38*W., 42 lks. dist.,
marked T 29 S R 1 W S 9 B T.

80.37 Intersect the old cor. of secs. 9, 10, 15 and 16, which
is a basalt stone, 5x15x6 ins. above ground, firmly set,
marked with 4 notches on S. and 3 notches on E. edges,
witnessed as described by the surveyor general. I
obliterate marks on the NE. and NW. bearing trees,
change this cor. to refer to secs. 15 and 16 only, and
mark 3 notches on W. edge of stone, from which

A fir, 10 ins. diam., bears S.10*E., 28 lks. dist.,
marked T 29 S R 1 W S 15 B T. (Old B T.)

A maple, 6 ins. diam., bears S.13*W., 94 lks. dist.,
marked T 29 S R 1 W S 16 B T. (Old B T.)