

107

Subdivisions, T. 29 S., R. 1 W.

CHAINS

76.20 Intersect the old cor. of secs. 10, 11, 14 and 15, which is a basalt stone, 5x7x5 ins. above ground, firmly set, marked with 4 notches on S. and 2 notches on E. edges, witnessed as described by the surveyor general. I obliterate marks on the NE. and NW. bearing trees, and change this cor. to refer to secs. 14 and 15 only, and mark 4 notches on W. edge of cor. from which

A cedar, 12 ins. diam., bears S.82\*E., 32 lks. dist., marked T 29 S R 1 W S 14 B T. (Old B T.)

A fir, 14 ins. diam., bears S.13\*W., 13 lks. dist., marked T 29 S R 1 W S 15 B T. (Old B T.)

Land, mountainous.

Soil, rocky loam, 3 rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, vinemaple, willow and salal.

S.89\*50'E., along the N. Bdy. of sec. 14.

Asc. SW. slope, 220 ft. to ridge, through heavy timber and dense undergrowth.

1.85 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 10, and 11, with brass cap marked

T29S	R1W
S10	S11
S14	
1922	

from which

A fir, 10 ins. diam., bears N. 54\*E., 102 lks. dist., marked T 29 S R 1 W S 11 B T.

A fir, 9 ins. diam., bears N.85\*W., 42 lks. dist., marked T 29 S R 1 W S 10 B T.

11.40 Top of ridge, bears NW. and SE., desc. NE. slope, 497 ft. to  $\frac{1}{4}$  sec. cor.