

111

Subdivisions, T. 29 S., R. 1 W.

CHAINS

firmly set, marked and witnessed as described by the surveyor general, I run S.89\*52'E., on a random calculated governing section line setting temp.  $\frac{1}{4}$  sec. and sec. cors. at each 40 and 80 chs., and, at 513.33 chs. fall 10 lks. S. of the cor. of secs. 1 and 12, on the E. Bdy. of the Tp.

-----


From the cor. of secs. 7 and 8, on the N. Bdy. of sec. 18 N.0\*01'E., bet. secs. 7 and 8.

Along E. slope through heavy timber and dense undergrowth.

3.51 Spring branch, 1 lk. wide, course E., continue along broken E. slope.

21.25 A huge boulder, bears E. 5 lks. dist., desc. steep NW. slope, 307 ft. to  $\frac{1}{4}$  sec. cor.

39.90 Point for  $\frac{1}{4}$  sec. cor., determined as hereinafter set forth. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap marked



from which

A sugar pine, 10 ins. diam., bears S. 68\*E., 10 lks. dist., marked  $\frac{1}{4}$  S 8 B T.

A fir, 24 ins. diam., bears S.58\*W., 11 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

Continue desc. 110 ft. to

46.52 Spring branch, 2 lks. wide, course E., continue gradual desc. 310 ft.

79.90 Intersect random governing section line, 4 lks. W. of the temp. cor. of secs. 5, 6, 7 and 8.

At the point of intersection,

A sugar pine, 12 ins. diam., for cor. of secs. 5, 6, 7 and 8; I mark

T 29 S S 5 on NE.,