

115

Subdivisions, T. 29 S., R. 1 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$
S8 | S9
1922

from which

A fir, 20 ins. in diam., bears N.13*E., 20 lks. dist., marked $\frac{1}{4}$ S 9 B T.

A fir, 20 ins. diam., bears N.43*W., 21 lks. dist., marked $\frac{1}{4}$ S 8 B T.

Desc. N. slope, 200 ft.

53.06 Spring branch, 1 lk. wide, course NE., asc. along E. slope, 53 ft.

59.80 Top of spur, slopes NE., desc. N. slope, 384 ft. to creek.

75.50 Desc. abruptly over precipitous bluffs 130 ft.

77.15 Creek, 6 lks. wide, course NE., asc. 46 ft. to

80.25 Top of small spur, slopes NE. desc.

80.54 Intersect random governing section line, 4 lks. E. of the temp. cor. of secs. 4, 5, 8 and 9.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap marked

T29S | R1W
S5 | S4
S8 | S9
1922

from which

A pine, 9 ins. diam., bears N.79*E., 17 lks. dist., marked T 29 S R 1 W S 4 B T.

A fir, 12 ins. diam., bears S.29*E., 8 lks. dist., marked T 29 S R 1 W S 9 B T.

A fir, 10 ins. diam., bears S.22*W., 14 lks. dist., marked T 29 S R 1 W S 8 B T.