

Subdivisions, T. 29 S., R. 1 W.

CHAINS

N.0*02'E., bet. secs. 4 and 5.

Desc. N. slope, 60 ft. through heavy timber and dense undergrowth.


5.91 South Fork of Dumore Creek, 20 lks. wide, course SE., asc. broken SW. slope, 672 ft. to $\frac{1}{4}$ sec. cor.

6.70 Spring branch, 2 lks. wide, course SW.

21.13 Spring branch, 3 lks. wide, course SE.

31.17 Gulch, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A fir, 30 ins. diam., bears N.25*E., 9 lks. dist., marked $\frac{1}{4}$ S 4 B T.

A fir, 20 ins. diam., bears S.73*W., 6 lks. dist., Marked $\frac{1}{4}$ S 5 B T.

Continue asc. of S. slope, 675 ft. to ridge.

42.40 Gulch, course SE.


77.80 Top of ridge, bears NW. and SE., desc. gradually, 10 ft.

80.80 Intersect the S. bdy. of T. 28 S., R. 1 W., 8.74 chs.

East from the $\frac{1}{4}$ sec. cor. of sec. 32.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap marked



from which

A fir, 10 ins. diam., bears S.32*E., 14 lks. dist., marked T 29 S R 1 W S 4 C C B T.

A fir, 14 ins. diam., bears S.29*W., 38 lks. dist.,