

Subdivisions, T. 29 S., R. 1 W.

CHAINS

From the cor. of secs. 10 and 11, on the N. bdy. of sec. 14;

N.0°03'E., bet secs. 10 and 11.

Asc. SW. slope, 290 ft. through heavy timber and dense undergrowth.

18.85 Top of ridge, bears NW. and SE., desc. gradually.

30.80 Desc. abrupt NE. slope, 211 ft. to

40.86 Point for  $\frac{1}{4}$  sec. cor., determined as hereafter set forth.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked



from which

A fir, 14 ins. diam., bears S.80°E., 8 lks. dist., marked  $\frac{1}{4}$  S 11 B T.

A madrona, 10 ins. diam., bears N.43°W., 13 lks. dist., marked  $\frac{1}{4}$  S 10 B T.

Desc. NE. slope, 217 ft. to

54.60 Bottom of desc. ascend along E. slope, 275 ft.

64.65 Top of spur, slopes NE., desc. N. slope, 254 ft.

74.70 Spring branch, 1 lk. wide, course NE., asc. abrupt S. slope, 280 ft.

80.86 Intersect random governing section line, 54 lks. E. of the temp. cor. of secs. 2, 3, <sup>10</sup> and 11.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 2, 3, 10 and 11, with brass cap marked



from which