

127

Subdivisions, T. 29 S., R. 1 W.

CHAINS	
40.17	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S2 $\frac{1}{4}$ S11 1922
	from which
	A fir, 16 ins. diam., bears N.4*E., 38 lks. dist., marked $\frac{1}{4}$ S 2 B T.
	A laurel, 6 ins. diam., bears S.33*W., 25 lks. dist., marked $\frac{1}{4}$ S 11 B T.
42.10	Creek, 3 lks. wide, course S., asc. along S. slope, 212 ft.
59.40	Top of asc. descend SE. slope, 402 ft. to
80.34	The cor. of secs. 1, 2, 11 and 12.
	Land, mountainous.
	Soil, rocky loam, 4th. rate.
	Timber, fir, pine, hemlock, cedar, madrona and chinquapin.
	Undergrowth, vine maple, salal and rhododendron.
	S.89*52'E., on a random line bet. secs. 1 and 12.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
112.45	Intersect E. bdy. of the Tp., 10 lks. S. of the cor. of secs. 1 and 12, which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general.
	Thence
	N.89*55'W., on a true line bet. secs. 1 and 12.
	Asc. NE. slope, 92 ft. through heavy timber and dense undergrowth.
6.05	Top of ridge, bears NW. and SE., desc. SW. slope, 202 ft.
17.03	Bottom of desc., asc. 211 ft.
22.95	Bluff 50 ft. high, continue asc. 135 ft. along S. slope.
44.95	Top of spur, slopes SW., desc. along N. side of spur, 366 ft.