

County Surveyor's Record, Douglas County, Oregon

A Portion of the West Boundary of T. 29 S., R. 1 W.
as surveyed by Fred Mensch, Deputy Surveyor, under
Contract No 757 Dated September 14, 1904.

CHAINS

I commence at the corner of Tps 29 and 30 S, Rs 1 and 2 W, which is partly obliterated. The old cor which was a post has disappeared and the pine described as bearing tree in Sec 1 has fallen and decayed. The other bearing trees are standing but the marks are deeply over grown.

I destroy the old marks and re-establish the corner in its original position as follows:

Set a basalt stone 18x12x6 ins 12 ins in the ground for cor of Tps 29 and 30 S, Rs 1 and 2 W, marked with 6 notches on each edge; from which

A black oak 24 ins diam bears N 2°E 83 lks dist marked T 29 S, R 1 W S 31 B T.

A red fir 10 ins diam bears S 12°E 20 lks dist marked T 30 S R 1 W S 6 B T.

A red fir 8 ins diam bears S 39°W 51 lks, dist marked T 30 S R 2 W S 1 B T.

A black oak 24 ins diam bears N 73°W 57 lks dist marked T 29 S R 2 W S 36 B T.

Thence I run

North bet secs 31 and 36

Over mountainous land through scattering timber and dense undergrowth.

Along W slope.

19.27 Gulch, course W.

40.00 Set a basalt stone 18x10x4 ins 12 ins in the ground for $\frac{1}{4}$ sec cor marked $\frac{1}{4}$ on W face; from which

A red fir 18 ins diam bears N 28°E 102 lks dist marked $\frac{1}{4}$ S 31 B T.

A sugar pine 40 ins diam bears N 61°W 74 lks dist marked $\frac{1}{4}$ S 36 B T.

40.25 Ridge point.

80.00 Set a basalt stone 15x10x6 ins 10 ins in the ground for cor of secs 25, 30, 31 and 36, marked with 5 notches on N and 1 notch on S edge; from which

A red fir 16 ins diam bears N 80°E 70 lks dist marked T 29 S R 1 W S 30 B T.

A red fir 12 ins diam bears S 66°E 56 lks dist marked T 29 S R 1 W S 31 B T.

A red fir 12 ins diam bears S 8°W 59 lks dist marked T 29 S R 2 W S 36 B T.

A laurel 6 ins diam bears N 17°W 55 lks dist marked T 29 S R 2 W S 25 B T.