

County Surveyor's Record, Douglas County, Oregon

North Boundary of T. 30 S., R. 2 W.

CHAINS

. only as follows:

Set a slate stone 18x15x10 ins. 10 ins. in the ground for 1/4 sec. cor. in E. boundary Sec. 36, marked 1/4 on W face, from which

A fir 30 ins. diam. bears S.15*W. 18 lks. dist. marked 1/4 S. 36 B T.

A Madrona 20 ins. diam. bears N.59*W. 70 lks. dist. marked 1/4 S 36 B T.

Land, mountainous.

Soil, clay and stony, 3rd and 4th rate.

Timber, fir, hemlock.

Undergrowth, snowbush, madone, hazel, vine maple.

Mountainous or heavily timbered land or land covered with dense undergrowth and exceptionally difficult to survey.

85.75 chs.

August 13, 1909..

Elmer F. Strickler

See Vol 16 p 6828

RESURVEY AND SURVEY OF NORTH AND EAST BOUNDARIES,
RESURVEY OF SOUTH AND WEST BOUNDARIES,
and
SURVEY OF SUBDIVISIONAL LINES

in

TOWNSHIP NO. 29 SOUTH, RANGE NO. 2 West.

Executed by Elmer F Strickler, *W. F. Strickler* under Special Instructions

Dated January 22, 1917.

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

Retracements

From the cor. of Tps. 29 and 30S., Rs. 1 and 2W., North retracing E. bdy. of sec. 36; at 39.64 chs. fall 26 lks. W. of the 1/4 sec. cor., and at 79.72 chs. fall 98 lks. W. of the cor. of secs. 25, 30, 31 and 36.

From the cor of secs. 25, 30, 31 and 36, North retracing E Bdy. of sec. 25; at 39.76 chs. fall 38 lks. W. of the 1/4 sec. cor., and at 79.89 chs. fall 48 lks. W. of the cor. of secs. 19, 24, 25 and 30.