

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

CHAINS

From the cor. of secs. 19, 24, 25 and 30, North retracing E. bdy. of sec. 24; at 40.38 chs. fall 13 lks. E. of the $\frac{1}{4}$ sec. cor., and at 80.11 chs. fall 54 lks. E. of the cor. of secs. 13, 18, 19 and 24.

From the cor. of secs. 13, 18, 19 and 24, North retracing E. bdy. of sec. 13; at 40.07 chs. fall 19 lks. W. of the $\frac{1}{4}$ sec. cor., and at 80.39 chs. intersect the cor. of secs. 7, 12, 13 and 18.

Commencing at the cor. of Tps. 29 and 30 S., Rs. 1 and 2 W., which is a basalt stone 18x12x6 ins., firmly set in the ground, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground for cor. of Tps. 29 and 30 S., Rs. 1 and 2 W., with brass cap marked

T29S
R2W R1W
S36 S31
S1 S6
T30S
1917

from which

A black oak, 24 ins. diam., bears N.2*E., 83 lks. dist., marked T 29 S R 1 W S 31 B T. (Old B.T.)

A red fir, 10 ins. diam., bears S12*E., 20 lks. dist. marked T 30 S R 1 W S 6 B T. (old B.T.)

A red fir, 8 ins. diam., bears S.39*W., 51 lks. dist., marked T 30 S R 2 W S 1 B T. (Old B.T.)

A black oak, 24 ins. diam., bears N.73*W., 57 lks. dist., marked T 29 S R 2 W S 36 B T. (old B.T.)

Thence

N.0*22'E., resurveying E. bdy. of sec. 36.

Along W. slope, through scattering timber and dense undergrowth.

19.03 Gulch, course W., ascend SW. slope.

28.14 Trail, bears NW. and SE.

39.64 Intersect the $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to Sec. 31, T. 29