

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

CHAINS

S., R. 1 W. only by destroying all markings referring to sec. 36 and marking $\frac{1}{4}$ on E. face. From cor.

A red fir, 36 ins. diam., bears East, 75 lks. dist., marked $\frac{1}{4}$ S 31 B T (New B.T.)

A red fir, 20 ins. diam., bears N.28°E., 102 lks. dist., marked $\frac{1}{4}$ S 31 B T (Old B.T.)

Thence

N.1°02'E., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$
S36
1917

from which

A pine, 48 ins. diam., bears S.88°30'W., 61 lks. Dist., marked $\frac{1}{4}$ S 36 B T.

A fir, 14 ins. diam., bears N.24°30'W., 79 lks. dist., marked $\frac{1}{4}$ S 36 B T.

40.50 Top of spur, slopes W., descend NW. slope.

47.68 Head of draw, course W., ascend.

79.73 Intersect the cor. of secs. 25, 30, 31 and 36, which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 30 and 31, T. 29 S., R. 1 W. only by destroying the marks ~~and~~^{and} bearing trees referring to secs. 25 and 36.

Thence

N.0°33'E., continuing my measurements

80.01 Set a basalt stone, 18x10x7 ins., 12 ins. in the ground, for cor. of secs. 25 and 36, marked with 5 notches on the N. and 1 notch on S. edge; from which

A fir, 10 ins. diam., bears S.5°30'W., 21 lks dist., marked T 29 S R 2 W S 36 B T.,

A Fir, 6 ins. diam. bears N.61°45'W., 48 lks. dist., marked T 29 S R 2 W S 25 B T.

Land, mountainous

Soil, rocky, 3rd rate.