

Resurvey and Survey of East Bdy., T. 29 S., R. 2 W.

CHAINS

Timber, fir, pine and cedar.

Undergrowth, maple, laurel and young timber.

N.0\*33'E., resurveying E. bdy. of sec. 25.

Ascend along SW slope, through heavy timber and dense undergrowth.

5.30 Creek, 2 lks. wide, course W.

17.07 Creek, 2 lks. wide, course W.

23.98 J. Rondew's barn bears N.68\*45'W., about 36.50 chs.

26.90 Top of spur, slopes SW., along W. slope.

37.00 Descend NW. slope.

39.49 Intersect the  $\frac{1}{4}$  sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 30, T. 29 S., R. 1 W. only by destroying all marks referring to sec. 25 and marking  $\frac{1}{4}$  on E. face. From cor.

A pine, 10 ins. diam., bears N.45\*E., 30 lks. dist., marked  $\frac{1}{4}$  S 30 B T. (Old B.T.)

A fir, 6 ins. diam. bears S.41\*45'E., 31 lks. dist., marked  $\frac{1}{4}$  S 30 B T (New B.T)

Thence

N.0\*09' E., continuing measurments.

40.00 Set an iron post, 3 feet long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 25 only, with brass cap marked

$\frac{1}{4}$   
 S25  
 1917

from which

A fir, 24 ins. diam., bears S.51\*45'W., 40 lks. dist., marked  $\frac{1}{4}$  S 25 B T.

A chinquapin, 8 ins. diam., bears N.28\*30'W., 53 lks. dist., marked  $\frac{1}{4}$  S 25 B T.

73.28 Creek, 2 lks. wide, course SW.

79.62 Intersect the cor. of secs. 19, 24, 25 and 30, which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to