

	Resurvey and Survey east Bdy., T. 29 S., R. 2 W.
CHAINS	<p>refer to secs. 19 and 30, T. 29 S., R. 1 W. only by destroying all marks referring to secs. 24 and 25.</p> <p>Thence</p> <p>N.0°11'W., continuing my measurements</p> <p>80.00 Set a basalt stone, 15x12x6 ins., 10 ins. in the ground, for cor. of secs. 24 and 25, marked with 4 notches on N. and 2 notches on S. edge; from which</p> <p style="padding-left: 40px;">A pine, 40 ins. diam., bears S.61°45'W., 56 lks. Dist., marked T 29 S R 2 W S 25 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N.33°30'W., 67 lks. dist., marked T 29 S R 2 W S 24 B T.</p> <p>Land, mountainous.</p> <p>Soil, rocky, 3rd rate.</p> <p>Timber, fir, pine and cedar.</p> <p>Undergrowth, rhododendron, chinquapin, and young timber.</p>
	<p>N.0°11'W., resurveying E. bdy. of sec. 24.</p> <p>Along W. slope, through heavy timber and dense undergrowth.</p> <p>2.77 Trail, bears E. and W.</p> <p>5.00 Ascend SW. slope.</p> <p>13.36 Top of spur, slopes SW., descend.</p> <p>27.54 Leave timber, bears E. and W., ascend.</p> <p>40.00 Intersect the <math>\frac{1}{4}</math> sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows; alongside the old cor.</p> <p style="padding-left: 40px;">Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., with brass cap marked</p> <div style="text-align: center; padding: 10px 0;"> <math display="block">\begin{array}{c} \frac{1}{4} \\ \text{S24} \mid \text{S19} \\ 1917 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A red fir, 20 ins. diam., bears N.20°E., 79 lks. dist. marked <math>\frac{1}{4}</math> S 19 B T (Old B.T.)</p> <p style="padding-left: 40px;">A red fir, 6 ins. diam., bears S.65°W., 185 lks. dist., marked <math>\frac{1}{4}</math> S 24 B T (Old B.T.)</p>