

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

CHAINS

Thence

N.0°35'W., continuing my measurements.

43.77 Trail, bears N.W. and SE.

47.74 Top of spur, slopes W., descend.

53.70 Enter heavy timber, bears NW. and SE.

60.00 Trail, bears NE. and SW.

63.05 Creek, 2 lks. wide, course SW.

65.36 Trail, bears NW. and SE.

79.73 Intersect the cor. of secs. 13, 18, 19 and 24, which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 18 and 19, T. 29 S., R. 1 W. only and destroy all marks referring to secs. 13 and 24.

Thence

N.0°16'E., continuing my measurements

80.00 Set a basalt stone, 18x12x8 ins., 12 ins. in the ground, for cor. of secs. 13 and 24, marked with 3 notches on N. and S. edges; from which

A fir, 14 ins. diam., bears S.54°W., 115 lks. dist., marked T 29 S R 2 W S 24 B T.

No other bearing tree available; raise a mound of stone, 2 ft. base, 1½ ft. high. W. of cor.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, willow, maple and wild lilac.

N.0°16'E., resurveying E. bdy. of sec. 13.

Ascend SW. slope, through heavy timber and dense undergrowth.

9.61 Trail, bears NE. and SW.

10.00 Creek, 3 lks. wide, course W.

29.50 Trail, bears NE. and SW.

33.00 Trail, bears NW. and SE.

39.80 Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor