

Resurvey and survey East Bdy., T. 29 S., R. 2 W.

CHAINS

. general. I change this cor. to refer to sec. 18, T. 29 S., R. 1 W. only by destroying all marks referring to sec. 13 and marking $\frac{1}{4}$ on E. face. from cor.

A fir, 16 ins. diam., bears N.86*E., 59 lks. dist.
marked $\frac{1}{4}$ S 18 B T. (Old B.T.)

A fir, 10 ins. diam., bears S.64*30'E., 26 lks. dist.,
marked $\frac{1}{4}$ S 18 B T (New B.T.)

Thence

N.0*16'W., continuing my measurments.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor of sec. 13 only, with brass cap marked

$\frac{1}{4}$
S13
1917

from which

A fir, 10 ins. diam., bears S.74*30'W., 131 lks. dist.,
marked $\frac{1}{4}$ S 13 B T.

A fir, 10 ins. diam., bears N.80*W., 70 lks. dist.,
marked $\frac{1}{4}$ S 13 B T.

56.00 Top of ridge, bears NW and SE., descend NE. slope.

63.80 Descend N. slope.

69.75 Along E. slope.

76.90 Top of spur, slopes E., descend.

80.00 Set a basalt stone, 20x20x16 ins., 15 ins. in the ground,
for cor. of secs. 12 and 13, marked with 2 notches on
N. and 4 notches on S. edge., from which

A hemlock 10 ins. diam., bears S.39*15'W., 54 lks.
dist., marked T 29 S R 2 W S 13 B T.

A fir, 36 ins. diam. bears N. 26*30'W., 70 lks. dist.,
marked T 29 S R 2 W S 12 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, fir, pine and hemlock.

Undergrowth, willow, lilac and hazel.

N.0*16'W., resurveying E. bdy. of sec. 12.