

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

CHAINS

Descend through heavy timber and dense undergrowth.

0.12 Intersect the cor. of secs. 7,12,13 and 18, which is a porphyry stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 7 and 18, T. 29 S., R. 1 W. only by destroying all marks referring to secs. 12 and 13.

Thence

North, surveying E. bdy. of sec. 12, and continuing my measurements.

31.60 Descend N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 12 only, with brass cap marked

$\frac{1}{4}$   
 S12  
 1917

from which

A pine, 6 ins. diam., bears S.43\*45'W., 42 lks. dist., marked  $\frac{1}{4}$  S 12 B T.

A fir, 12 ins. diam., bears N.82\*W., 6 lks. dist., marked  $\frac{1}{4}$  S 12 B T.

40.12 Set a basalt stone, 15x8x8 ins., 10 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 7, T. 29 S., R. 1 W. only, marked  $\frac{1}{4}$  on E. face; from which

A fir, 36 ins. diam., bears N.45\*15'E., 52 lks. dist., marked  $\frac{1}{4}$  S.7 B T.

A fir, 16 ins. diam., bears S.43\*E., 14 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

43.44 Creek, 4 lks. wide, course NE., ascend.

49.60 Top of spur, slopes E., descend.

53.50 Creek, 10 lks. wide, course SE., ascend.

62.00 Top of ascent. along E. Slope.

71.55 Creek, 2 lks. wide, course E., ascend.

73.50 Top of spur, slopes E. descend.

75.20 Creek, 2 lks. wide, course SE., ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 1 and 12, with brass cap marked