

## County Surveyor's Record, Douglas County, Oregon

Resurvey and Survey East Bdy., T. 29 S., R. 2 W.

CHAINS

T29S
S1
S12
R2W
1917

from which

A pine, 12 ins. diam., bears S.25\*30'W., 41 lks. dist.,  
marked T 29 S R 2 W S 12 B T.

A Fir, 12 ins. diam., bears N.35\*W., 21 lks. dist.,  
marked T 29 S R 2 W S 1 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, pine and fir.

Undergrowth, willow, hazel, manzanita and chinquapin.

North, along the E. bdy. of Sec. 1

Along E slope, through scattering timber and undergrowth.

0.12 Set a basalt stone, 15x10x8 ins. 10 ins. in the ground,  
for cor. of secs. 6 and 7, T. 29 S., R. 1 W. only,  
marked with 1 notch on N. and 5 notches on S. edge; from  
which

A pine, 18 ins. diam., bears N.36\*30'E., 73 lks. dist.,  
marked T 29 S R 1 W S 6 B T.

A fir, 10 ins. diam., bears S.45\*30'E., 24 lks. dist.,  
marked T 29 S R 1 W S 7 B T.

13.30 Creek, 2 lks. wide, course E., ascend.

21.80 Top of spur, slopes E., descend.

35.67 (This point is East 123.62 chs. from the cor. of secs. 34  
and 35, on the S bdy. of T. 28 S., R. 2 W., as deter-  
mined by a random line)

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in  
the ground, for the NE. cor. of T. 29 S., R. 2 W., with  
brass cap marked

S1
T29S
R2W
1917