

46
X

County Surveyor's Record, Douglas County, Oregon

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

- From the cor. of Tps. 29 and 30 S., Rs. 1 and 2 W., previously described
- West, resurveying S. bdy. of sec. 36.
- Descend W. slope, through heavy timber and dense undergrowth.
- 39.20 Creek, 10 lks. wide, course S., ascend.
- 39.61 Intersect the $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 1, T. 30 S., R. 2 W. only by destroying all marks referring to sec. 36 and mark $\frac{1}{4}$ on S. face. From cor.
- A fir, 6 ins. diam., bears S.7*45'W., 53 lks. dist., marked $\frac{1}{4}$ S 1 B T (New B.T.)
- A fir, 8 ins. diam., bears S.20*E., 46 lks. Dist., marked $\frac{1}{4}$ S 1 B T (Old B.T.)
- Thence
- N.89*53'W., continuing my measurments
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 36 only, with brass cap marked
- $\frac{1}{4}$ S36
- 1917
- from which
- A fir, 10 ins. diam., bears N.44*45'E., 18 lks. dist., marked $\frac{1}{4}$ S 36 B T.
- A fir, 14 ins. diam., bears N.37*W., 47 lks. dist., marked $\frac{1}{4}$ S 36 B T.
- 50.79 Top of spur, slopes S., descend.
- 62.50 Deadman Creek, 30 lks. wide, course S.E.; ascend.
- 69.50 Top of spur, slopes NE.; ascend along NE slope.
- 79.45 Intersect the cor. of secs. 1, 2, 35 and 36, which is a stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 1 and 2, T. 30 S., R. 2 W. only by destroying all marks referring to secs. 35 and 36. From cor.
- A fir, 5 ins. diam., bears S.11*E., 36 lks. dist., marked T 30 S R 2 W S 1 B T. (Old B.T.)