

47
X

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

A Fir, 15 ins. diam., bears S.43*W., 85 lks. dist.,
marked T 30 S R 2 W S 2 B T (New B.T.)

Thence

S.89*45'W., continuing my measurements.

80.00 Set a basalt stone, 18x13x6 ins., 12 ins. in the ground, for
cor. of secs. 35 and 36, marked with 1 notch on E. and 5
notches on W. edge; from which

A fir, 30 ins. diam., bears N.45*30'E., 19 lks. dist.,
marked T 29 S R 2 W S 36 B T.

A fir, 15 ins. diam., bears N.4~~5~~*W., 58 lks. dist.,
marked T 29 S R 2 W S 35 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, maple and willow.

S.89*45'W., resurveying S. Bdy. of Sec. 35.

Ascend through heavy timber and dense undergrowth.

17.00 Top of ascend; along N. slope.

21.00 Descend NW. slope.

30.00 Creek, 5 lks. wide, course NE., ascend.

36.50 Old trail, bears N. and SW.

36.76 Top of spur, slopes NE.; along N. slope.

39.43 Intersect the $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly
set, marked and witnessed as described by the surveyor
general. I change this cor. to refer to sec. 2 $\frac{1}{2}$ T. 30 S.,
R. 2 W. only by destroying all marks referring to sec. 35
and marking $\frac{1}{4}$ on S. face. From cor.

A hemlock, 8 ins. diam., bears S.63*W., 73 lks. dist.,
marked $\frac{1}{4}$ S 2 B T (New B.T.)

A fir, 20-ins. diam., bears S.84*E., 37 lks. dist.,
marked $\frac{1}{4}$ S 2 B T (Old B.T.)

Thence

N.89*40'W., continuing my measurements.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the