

## Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

ground, for  $\frac{1}{4}$  cor. of sec. 35 only, with brass cap marked

1S35

1917

from which

A fir, 15 ins. diam., bears N.56\*30'E., 69 lks. dist.,  
marked  $\frac{1}{4}$  S 35 B T.

A Balsam fir, 15 ins. diam., bears N.51\*15'W., 58 lks.  
dist., marked  $\frac{1}{4}$  S 35 B T.

42.70 Creek, 4 lks. wide, course NE., ascend.

46.00 Creek, 4 lks. wide, course SE., comes from W., ascend along  
creek.

50.80 Leave creek, comes from SW. and flows E.

60.32 Creek, 2 lks. wide, course N.E.

79.00 Spring branch, course SE.

79.49 Intersect the cor. of secs. 2, 3, 34 and 35, which is a  
basalt stone, firmly set, marked and witnessed as de-  
scribed by the surveyor general. I change this cor. to  
refer to secs. 2 and 3, T. 30 S., R. 2 W. only by de-  
stroying all marks referring to secs. 34 and 35. From  
cor.

A fir, 6 ins. diam., bears S.32\*45'E., 23 lks. dist.  
marked T 30 S R 2 W S 2 B T. (Old B.T.)

A fir 10 ins. diam., bears S.66\*30'W., 23 lks. dist.,  
marked T.30 S R 2 W S 3 B T ( Old B.T. )

Thence

S.89\*54'W., continuing my measurements.

80.00 Set a basalt stone, 18x12x4 ins., 12 ins. in the ground,  
for cor. of secs. 34 and 35, marked with 2 notches on E.  
and 4 notches on W. edge; from which

A Fir, 24 ins. diam., bears N.32\*30'E., 57 lks. dist.,  
marked T 29 S R 2 W S 35 B T.

A fir, 40 ins. diam., bears N.12\*30'W., 47 lks. dist.,  
marked T 29 S R 2 W S 34 B T.

Land, mountainous.

Soil, rocky, 3rd rate.