

County Surveyor's Record, Douglas County, Oregon

6247

X

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

Timber, fir, pine and cedar.
Undergrowth, maple.

S.89*54'W., resurveying S. bdy. sec. 34.

Ascend E. slope, through heavy timber and dense undergrowth.

17.00 Top of spur, slopes SE., descend.

22.65 Enter swamp, bears N. and S.

25.15 Leave swamp; ascend SE. slope.

33.43 Trail to Schultz's homestead, bears N. and S.

39.60 Intersect the $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 3, T. 30 S., R. 2 W. only by destroying all marks referring to Sec. 34 and marking $\frac{1}{4}$ on S. face. From cor.

A fir, 18 ins. diam., bears S.1*W., 48 lks. dist., marked $\frac{1}{4}$ S 3 B T (Old B.T.)

A fir, 14 ins. diam., bears S.25*W., 45 lks. dist., marked $\frac{1}{4}$ S 3 B T. (New B.T.)

thence

S.89*45'W., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of ⁵34 only, with brass cap marked

$\frac{1}{4}$ S34

1917

from which

A fir, 14 ins. diam., bears N.18*15'E., 52 lks. dist., marked $\frac{1}{4}$ S 34 B T.

A fir, 18 ins. diam., bears N.72*30'W., 30 lks. dist., marked $\frac{1}{4}$ S 34 B T.

70.80 Top of ridge, bears NE. and SW. descend.

Trail along top of ridge, bears NE. and SW.

79.59 Intersect the cor. of secs. 3, 4, 33 and 34, which is a fir tree, 48 ins. diam., marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 3 and 4, T. 30 S., R. 2 W. only by destroying