

County Surveyor's Record, Douglas County, Oregon

Resurvey South Bdy., T. 29 S., R 2 W.

CHAINS

all marks referring to secs. 33 and 34. from cor.

A fir, 8 ins. diam., bears S.35*E., 73 lks. dist.,
marked T.30 S R 2 W S 3 B T (Old B.T.)

A cedar, 5 ins. diam., bears S.89*W., 49 lks. dist.,
marked T 30 S R 2 W S 4 B T. (Old B.T.)

Thence

S.89*53'W., continuing my measurements.

80.00 Set a basalt stone 15 x 10 x 8 ins., 10 ins. in the ground,
for cor. of secs. 33 and 34, marked 3 notches on E. and
W. edges, from which

A fir, 14 ins. diam., bears N.5*E., 105 lks. dist.,
marked T 29 S R 2 W S 34 B T.

A cedar, 12 ins. diam., bears N.30*30'W., 59 lks. dist.,
marked T.29 S R 2 W S 33 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, young timber, rhododendron, chinquapin and
salal.

S.89*53'W., resurveying S. bdy. of sec. 33.

Descend N.W. slope, through heavy timber and dense undergrowth.

3.50 Foot of descent; ascend NE. slope.

10.00 Trail, bears NE. and SW.

12.50 Top of ascent; descend NW. slope.

24.50 Head of draw, course N.; ascend NE. slope.

31.90 Top of spur, slopes N.; descend NW. slope.

39.25 Creek, 1 lk. wide, course N.

39.36 Intersect the $\frac{1}{4}$ sec. cor., which is a slate stone, firmly
set, marked and witnessed as described by the surveyor
general. I change this cor. to refer to sec. 4, T. 30S.
R. 2 W. only by destroying all marks referring to sec.
33 and marking $\frac{1}{4}$ on S. face. From cor.

A fir, 32 ins. diam., bears S.20*E., 37 lks. dist.,
marked $\frac{1}{4}$ S 4 B T. (New B.T.)