

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

A Cedar, 14 ins. diam., bears S.20*W., 48 lks. dist.,
marked $\frac{1}{4}$ S 4 B T (Old B.T.)

Thence

S.89*45'W., continuing my measurments.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ ^{sec} cor. of sec. 33 only, with brass cap marked

$\frac{1}{4}$ S33

1917

from which

A cedar, 12 ins. diam., bears N.20*30'E., 105 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.

A fir, 28 ins. diam., bears N.56*W., 73 lks. dist.,
marked $\frac{1}{4}$ S 33 B T.

51.50 Across earth slide to the north.

57.00 Leave slide; ascend N.E. slope.

73.00 Top of ridge, bears NW. and SE.; descend.

74.30 U. S. Forest Service trail and telephone line, Tiller to
Peel, bears NW. and SE.

79.05 Intersect the cor. of Secs. 4, 5, 32 and 33, which is a
porphyry stone, firmly set, marked and witnessed as de-
scribed by the surveyor general. I change this cor. to
refer to secs. 4 and 5, T. 30 S., R. 2 W. only by de-
stroying all marks referring to secs. 32 and 33. From
cor.

A fir, 30 ins. diam., bears S.29*E., 6 lks. dist.,
marked T 30 S R 2 W S 4 B T (Old B.T.)

A cedar, 12 ins. diam. bears S.22*30'W., 21 lks. dist.,
marked T 30 S R 2 W S 5 B T (Old B.T.)

Thence

S.89*55'W., continuing my measurements

80.00 Set a granite stone, 18x7x7 ins., 12 ins. in the ground,
for cor. of secs. 32 and 33, marked with 4 notches on E
and 2 notches on W. edge; from which

A fir, 36 ins. diam., bears N.21*15'E., 51 lks. dist.,
marked T 29 S R 2 W S 33 B T.