

6220
37
X

County Surveyor's Record, Douglas County, Oregon

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS	
	<p>A balsam fir 15 ins. diam., bears N.64*45'W., 56 lks. dist., marked T 29 S R 2 W S 32 B T.</p> <p>Land, mountainous.</p> <p>Soil, rocky, 3rd rate.</p> <p>Timber, cedar, fir, pine and hemlock.</p> <p>Undergrowth, maple, laurel, young timber and salal.</p>
	<p>S.89*55'W., resurveying S. bdy. of sec. 32.</p> <p>Ascend through heavy timber and dense undergrowth.</p>
24.25	Top of spur, slopes NW., descend.
38.88	<p>Intersect the $\frac{1}{4}$ sec. cor.; which is a porphyry stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 5, T. 30 S., R. 2 W. only by destroying all marks referring to sec. 32 and marking $\frac{1}{4}$ on S. face. From cor.</p> <p>A fir, 28 ins. diam., bears S.62*W., 70 lks. dist., marked $\frac{1}{4}$ S 5 B T (New B.T.)</p> <p>A madrona, 12 ins. diam., bears S.10*30'E., 56 lks. dist., marked $\frac{1}{4}$ S 5 B T (Old B.T.)</p> <p>Thence</p> <p>S.89*53'W., continuing my measurements</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for $\frac{1}{4}$ cor of sec. 32 only, with brass cap marked</p> <p style="text-align: center;"><u>$\frac{1}{4}$S32</u></p> <p style="text-align: center;">1917</p> <p>from which</p> <p>A fir, 10 ins. diam., bears N.14*15'E., 39 lks. dist., marked $\frac{1}{4}$ S 32 B T.</p> <p>A fir, 14 ins. diam., bears N.34*30'W., 59 lks. dist., marked $\frac{1}{4}$ S 32 B T.</p>
45.00	Ascend along S. slope.
49.00	Top of spur, slopes SW.; descend.
61.80	Trail, bears NE. and SW.
63.10	Mining ditch, course S.
64.35	Creek 4 lks. wide, in Texas Gulch, course SW.; ascend.