

~~33~~

Resurvey, South Bdy., T. 29 S., R. 2 W.

CHAINS

- 67.60 Mining ditch, course S.W.
- 75.70 Top of spur, slopes SW.; along S. slope.
- 78.88 Intersect the cor. of secs. 5, 6, 31 and 32, which is a quartz stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 5 and 6, T. 30 S., R. 2 W. only by destroying all marks referring to secs. 31 and 32. From cor.
- A fir, 24 ins. diam., bears S.27*E., 18 lks. dist., marked T 30 S R 2 W S 5 B T (Old B.T.)
- A fir, 30 ins. diam., bears S.16*W., 46 lks. dist., marked T 30 S R 2 W S 6 B T (Old B.T.)
- Thence
- S.89*51'W., continuing my measurements
- 80.00 Set a porphyry stone, 15x12x6 ins., 10 ins. in the ground, for cor. of secs. 31 and 32, marked with 5 notches on E. and 1 notch on W. edge; from which
- A fir, 10 ins. diam., bears N.6*30'E., 21 lks. dist., marked T 29 S R 2 W S 32 B T.
- A fir, 20 ins. diam., bears N.38*15'W., 54 lks. dist., marked T 29 S R 2 W S 31 B T.
- Land, mountainous.
- Soil, rocky loam, 3rd rate.
- Timber, fir, cedar, pine and hemlock
- Undergrowth, snowbrush, maple, rhododendron and young timber.
-
- S.89*51'W., resurveying S. bdy. of sec. 31.
- Ascend SE. slope, through heavy timber and dense undergrowth,
- 8.60 Top of spur, slopes S.; along S. slope.
- 12.60 Descend SW. slope.
- 15.50 Gulch, course S.; ascend.
- 30.60 Top of spur, slopes S.; descend.
- 34.10 Head of draw, course SE.; ascend.
- 38.68 Intersect the $\frac{1}{4}$ sec. cor., which is a porphyry stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 6, T. 30 S.,