

6222
34

County Surveyor's Record, Douglas County, Oregon

Resurvey South Bdy., T. 29 S., R. 2 W.

CHAINS

R. 2 W. only by destroying all marks referring to sec. 31 and marking $\frac{1}{4}$ on S. face. From cor.

A fir, 12 ins. diam., bears S.2*15'E., 20 lks dist., marked $\frac{1}{4}$ S 6 B T. (New B.T.)

A madrona, 6 ins. diam., bears S.40*E., 3 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S 6 B T (Old B.T.)

Thence

S.89*49'W., continuing my measurements

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 31 only, with brass cap marked

$\frac{1}{4}$ S31
1917

from which

A fir, 20 ins. diam., bears N.8*30'E., 19 lks. dist., marked $\frac{1}{4}$ S 31 B T.

A fir, 30 ins. diam., bears N.32*30'W., 30 lks. dist., marked $\frac{1}{4}$ S 31 B T.


67.00 Coffee Creek, 15 lks. wide, course S.; ascend SE. slope.

78.00 Top of spur, slopes S.; descend SW. slope.

84.80 Spring branch, 1 lk. wide, course SE.

84.87 Intersect the closing cor. of Tps. 29 and 30 S., R. 2 W., which is a slate stone, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows; alongside the old cor.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for closing cor. of Tps. 29 and 30 S., R. 2 W., with brass cap marked



from which

A hemlock, 12 ins. diam., bears N.44*E., 22 lks. dist., marked T 29 S R 2 W S 31 B T (Old B.T.)