

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS	
	by the surveyor general.
	Thence
	N.0*13'W., continuing my measurements
7.00	Top of spur, slopes SE.; along E. slope.
17.90	Descends NE. slope.
28.00	Creek, 2 lks. wide, course SE.; ascend SW. slope.
38.20	Top of spur, slopes SW.; along W. slope.
40.00	Set a basalt stone, 15x10x8 ins., 10 ins., in the ground, for $\frac{1}{4}$ cor. of sec. 31 only, marked $\frac{1}{4}$ on E. face; from which A Fir, 18 ins. diam., bears S.87*30'E., 69 lks. dist., marked $\frac{1}{4}$ S 31 B T. A laurel, 10 ins. diam., bears S.30*E., 58 lks. dist., marked $\frac{1}{4}$ S 31 B T.
45.04	Intersect the old cor. of secs. 25, 30, 31 and 36, which is a badly decayed post, marked and witnessed as described by the surveyor general, with the exception that the NE. bearing tree has been destroyed. I change this cor to refer to Secs. 25 and 36, T. 29 S., R. 3 W. only and perpetuate it as follows; alongside the old cor. Set a basalt stone, 15x8x7 ins., 10 ins. in the ground, for cor. of secs. 25 and 36, T. 29 S., R. 3 W. only, marked with 1 notch on S. and 5 notches on N. edge; from which A fir, 16 ins. diam., bears S.65*W., 45 lks. dist., marked T.29 S R 3 W S 36 B T (Old B.T.) A fir, 10 ins. diam., bears N.75*W., 35 lks. dist., marked T 29 S R 3 W S 25 B T (Old B.T.)
	Thence
	N.0*36'W., continuing my measurements
48.90	Ascend SE. slope.
53.70	Top of spur, slopes E.; descend.
57.55	Creek, 3 lks. wide, course E.; ascend.
64.45	Top of spur, slopes E.; descend.
68.00	Gulch, course SE.; ascend.
80.00	Set an iron post, 3 feet, long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 30 and 31, with brass cap marked