

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS

T29S
S30
S31
R2W
1917

from which

A fir, 28 ins. diam., bears N.16*15'E., 78 lks. dist.,
marked T 29 S R 2 W S 30 B T.

A fir, 38 ins. diam., bears S.16*30'E., 161 lks. dist.,
marked T 29 S R 2 W S 31 B T.

Land, rolling and mountainous.

Soil, rocky, 3rd rate.

Timber, fir, cedar and hemlock.

Undergrowth, snowbrush, rhododendron and salal.

N.0*36'W., resurveying W. bdy. of sec. 30.

Ascend through heavy timber and dense undergrowth.

2.82 Intersect the old $\frac{1}{4}$ sec. cor., which is a badly decayed
post, marked and witnessed as described by the surveyor
general. I change this cor. to refer to sec. 25 only and
perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 25, T. 29 S., R. 3 W. only,
with brass cap marked

$\frac{1}{4}$
S25
1917

from which

A fir, 24 ins. diam. bears S.14*W., 59 lks. dist.,
marked $\frac{1}{4}$ S 25 B T. (New B.T.)

A fir, 20 ins, diam., bears N.8*W., 249 lks. dist.,
marked $\frac{1}{4}$ S 25 B T (New B.T.)

Thence

North, continuing my measurements

10.20 Top of spur, slopes E., descend.

23.60 Creek, 3 lks. wide, course E., ascend.

33.10 Creek, 1 lk. wide, course SE.; continue ascent.

40.00 Set a basalt stone, 15x9x6 ins., 10 ins. in the ground