

County Surveyor's Record, Douglas County, Oregon

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS

for $\frac{1}{4}$ cor. of sec. 30 only, marked $\frac{1}{4}$ on E. face; from which

A fir, 18 ins. diam., bears S.25*E., 18 lks. dist., marked $\frac{1}{4}$ S 30 B T.

A fir, 32 ins. diam., bears N.65*E., 86 lks. dist., marked $\frac{1}{4}$ S.30 B T.

40.81 Intersect the point for old cor. of secs. 19, 24, 25 and 30, established by references to the SW. and NW. bearing trees as described by the surveyor general; all other traces of the cor. have disappeared. I change this cor. to refer to secs. 24 and 25 only and perpetuate it as follows; at the exact cor. point

Set a basalt stone, 15x10x8 ins., 10 ins. in the ground, for cor. of secs. 24 and 25, T. 29 S., R. 3 W. only, marked with 2 notches on S. and 4 notches on N. edge; from which

A cedar, 18 ins. diam., bears S.10*W., 13 lks. dist., marked T 29 S R 3 W S 25 B T.

A fir, 24 ins. diam., bears N.18*W., 46 lks. dist., marked T 29 S R 3 W S 24 B T.

Thence

N.0*28'W., continuing my measurements

55.80 Top of spur, slopes SE.; along broken E. slope.

79.76 Intersect the old $\frac{1}{4}$ sec. cor., which is a badly decayed post, firmly set in the ground, witnessed as described by the surveyor general. I change this cor. to refer to sec. 24 only and perpetuate it as follows; alongside the old cor.

Set a basalt stone, 15x10x8 ins., 10 ins. in the ground for $\frac{1}{4}$ cor. of sec. 24, T. 29 S., R. 3 W. only, marked $\frac{1}{4}$ on W. face; from which

A fir, 32 ins. diam., bears S.34*15'W., 52 lks. dist., marked $\frac{1}{4}$ S 24 B T. (New B.T.)

A fir, 30 ins. diam., bears N.70*W., 26 lks. dist., marked $\frac{1}{4}$ S 24 B T (Old B.T.)