

County Surveyor's Record, Douglas County, Oregon

6227

39

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS

Thence

N.1*23'E., continuing my measurements

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 19 and 30, with brass cap marked

T29S
S19
S30
R2W
1917

from which

A fir, 36 ins. diam., bears N.53*15'E., 22 lks. dist., marked T.29 S R 2 W S 19 B T.

A fir, 30 ins. diam., bears S.54*E., 32 lks. dist., marked T 29 S R 2 W S 30 B T.

Land, mountainous.

Soil, light loam, dry and gravelly, 2nd and 3rd rate.

Timber, fir, pine, cedar and hemlock.

Undergrowth, maple, young timber and chinquapin.

N.1*23'E., resurveying W. bdy. of sec. 19.

Ascend SE. slope, through heavy timber and dense undergrowth

8.70 Top of ridge, bears NE. and SW.; descend.

Trail along top of ridge, bears NE and SW.

30.50 Leave live timber; enter burn, bears NW. and SE.

39.81 Apportioned distance

Set a basalt stone, 15x7x6 ins., 10 ins. in the ground, for cor. of secs. 13 and 24, T. 29 S., R. 3 W. only, marked with 3 notches on N. and S. edges; from which

A fir, 36 ins. diam., bears S.71*W., 186 lks. dist., marked T 29 S R 3 W S 24 B T.

A fir, 32 ins., diam., bears N.17*W., 257 lks. dist., marked T 29 S R 3 W S 13 B T.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 19 only, with brass cap marked

$\frac{1}{4}$
S19
1917

from which