

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS

39.89 Intersect the old cor. of secs. 7, 12, 13 and 18, which is a badly decayed post, witnessed by the SE. bearing tree as described by the surveyor general, all other traces of the cor. have disappeared. I change this cor to refer to secs. 12 and 13 only and perpetuate it as follows; alongside the old cor.

Set a basalt stone, 18x7x5 ins., 12 ins. in the ground, for cor. of secs. 12 and 13, T. 29 S., R. 3 W. only, marked with 4 notches on S. and 2 notches on N. edge; from which

A fir, 15 ins. diam., bears S.55*W., 35 lks. dist., marked T 29 S R 3 W S 13 B T.

A fir, 20 ins. diam., bears N.68*15'W., 47 lks. dist., marked T 29 S R 3 W S 12 B T.

Thence

N.0*56'W., continuing my measurements

40.01 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 18 only, with brass cap marked

$\frac{1}{4}$
S 18
1917

from which

A fir, 20 ins. diam., bears N.31*15'E., 65 lks. dist., marked $\frac{1}{4}$ S 18 B T.

A fir, 20 ins. diam., bears S.84*E., 46 lks. dist., marked $\frac{1}{4}$ S 18 B T.

63.20 Top of spur, slopes SE.; ascend along SE. slope.

79.66 Intersect the old $\frac{1}{4}$ sec. cor., which is a post, badly decayed, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 12 only, and perpetuate it, as follows; alongside the old cor.

Set a basalt stone, 14x10x5 ins., 9 ins. in the ground, for $\frac{1}{4}$ cor of sec. 12, T. 29 S., R. 3 W. only, marked $\frac{1}{4}$ on W. face; from which

A fir, 24 ins. diam., bears West, 16 lks. dist., marked $\frac{1}{4}$ S 12 B T (Old B.T.)