

6230
47
X

County Surveyor's Record, Douglas County, Oregon

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS

A fir, 24 ins. diam., bears S.50*15'W., 67 lks. dist.,
marked 1/4 S 12 B T (New B.T.)

Thence

N.1*44'E., continuing my measurements

80.02 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the
ground, for cor. of secs. 7 and 18, with brass cap marked

T29S
S7
S18
R2W
1917

from which

A cedar, 12 ins. diam., bears N.17*45'E., 43 lks. dist.
marked T 29 S R 2 W S 7 B T.

A fir, 12 ins. diam., bears S.47*15'E., 71 lks. dist.,
marked T 29 S R 2 W S 18 B T.

Land, mountainous.

Soil, rocky and gravelly, 3rd rate.

Timber, fir, pine and cedar.

Undergrowth, rhododendron, madrona and chinquapin.

N.1*44'E., resurveying W. bdy. of sec. 7

Descend SE. slope, through heavy timber and dense undergrowth.

6.00 Creek, 2 lks. wide, course SE.; ascend.

38.38 Intersect the old cor. of secs. 1, 6, 7 and 12, which is a
badly decayed post, marked and witnessed as described by
the surveyor general, with the exception that the NE.
bearing tree has been destroyed. I change this cor. to
refer to secs. 1 and 12 only and perpetuate it as follows;
alongside the old cor.

Set a basalt stone, 16x10x5 ins., 12 ins. in the ground,
for cor. of secs. 1 and 12, T. 29 S., R. 3 W. only, marked
with 5 notches on S. and 1 notch on N. edge; from which

A fir, 36 ins. diam., bears S.20*W., 18 lks. dist.,
marked T 29 S R 3 W S 12 B T. (Old B.T.)

A fir, 34 ins. diam., bears N.48*W., 50 lks. dist.,
marked T 29 S R 3 W S 1 B T. (Old B.T.)