

Resurvey West Bdy., T. 29 S., R. 2 W.

CHAINS	<p>Thence</p> <p>N.0°52'W., continuing my measurements</p> <p>40.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 7 only, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ S7 1917 </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 36 ins. diam., bears N.71°30'E., 47 lks. dist., marked $\frac{1}{4}$ S 7 B T.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S.80°E., 30 lks. dist., marked $\frac{1}{4}$ S 7 B T.</p> <p>44.00 Top of ridge, bears E. and W.; descend.</p> <p>78.76 Intersect the old $\frac{1}{4}$ sec. cor., which is a badly decayed post standing in rock slide, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 1 only and perpetuate it as follows;</p> <p>On the W. side of the (old cor. is a boulder in place, 5x4x3 ft. above ground, which I mark with a cross (x) for $\frac{1}{4}$ cor. of sec. 1, T. 29 S., R. 3 W. only and mark $\frac{1}{4}$ W of cross; from which</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears N.64°W., 30 lks. dist., marked $\frac{1}{4}$ S I B T.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam. bears S.22°W., 43 lks. dist., marked $\frac{1}{4}$ S 1 B T.</p> <p>Thence</p> <p>N.4°01'E., continuing my measurements</p> <p>80.02 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in a rock slide, for cor. of secs. 6 and 7, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> T29S S6 <hr style="width: 20px; margin: 0 auto;"/> S7 R2W 1917 </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N.38°45'E., 96 lks. dist., marked T 29 S R 2 W S 6 B T.</p>
--------	--