

## Resurvey and Survey North Bay T. 29 S., R. 2 W.

CHAINS

from which

A fir, 14 ins. diam., bears S.14\*E., 62 lks. dist.,  
marked  $\frac{1}{4}$  S 6 B T.

A fir, 18 ins. diam., bears S.80\*W., 35 lks. dist.,  
marked  $\frac{1}{4}$  S 6 B T.

42.90 Top of spur, slopes S.

47.40 Leave burned timber; enter heavy green timber, bears NE.  
and SW.

51.65 Myrtle Creek, 20 lks. wide, course SW.; ascend.

65.00 Creek, 2 lks. wide, course NW.

66.49 Same creek, course SW.

69.70 Same creek, course NW.

78.50 Intersect the  $\frac{1}{4}$  cor. of sec. 31, which is a badly decayed  
post, marked and witnessed as described by the surveyor  
general; I, perpetuate this cor., as follows: alongside  
the old cor.

Set a conglomerate stone, 15x7x5 ins., 10 ins. in the  
ground for  $\frac{1}{4}$  cor. of sec. 31, T. 28 S., R. 2 W. only  
marked  $\frac{1}{4}$  on N. face from which

A cedar, 9 ins. diam., bears N.6\*E., 20 lks dist.,  
marked  $\frac{1}{4}$  S 31 B T (Old B.T.)

A cedar, 20 ins. diam., bears N.17\*30\*W., .19 lks. dist.,  
marked  $\frac{1}{4}$  S 31 B T (New B.T.)

Thence

N.89\*59'E., continuing my measurements

82.06 Set a conglomerate stone, 15x10x5 ins., 10 ins. in the  
ground, for cor. of secs. 5 and 6, marked with 1 notch on  
W. and 5 notches on E. edge; from which

A hemlock, 18 ins. diam., bears S.59\*E., 28 lks. dist.,  
marked T. 29 S R 2 W S 5 B T.

A cedar, 18 ins. diam., bears S.14\*W., 22 lks. dist.,  
marked T 29 S R 2 W S 6 B T.

Land, mountainous.

Soil, rocky, 3rd rate.

Timber, fir, cedar and pine.