

Resurvey and Survey North Bdy., T. 29 S., R. 2 W.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 4 only, with brass cap marked

$\frac{1}{4}$ S4
1917

From which

A fir, 44 ins. diam., bears S.86*15'E., 71 lks. dist., marked $\frac{1}{4}$ S 4 B T.

A fir, 40 ins. diam., bears S.14*W., 38 lks. dist., marked $\frac{1}{4}$ S 4 B T.

44.75 Head of draw, course N.; ascend.

49.40 U.S. Forest Service trail and telephone line, Tiller to Peel, bears N. and S.

51.80 Top of ridge, bears NE. and SW.; along S. slope.

57.20 Creek, 1 lk. wide, course S.; ascend.

71.80 Top of spur, slopes SE.; descend.

76.09 Intersect the $\frac{1}{4}$ cor. of sec. 33, which is a fir post, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor. as follows: alongside the old cor.

Set a basalt stone, 15x8x6 ins., 10 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 33, T. 28 S., R. 2 W. only, marked $\frac{1}{4}$ on N. face; from which

A fir, 8 ins. diam., bears N.38*30'E., 29 lks. dist., marked $\frac{1}{4}$ S 33 B T. (New B.T.)

A fir, 10 ins. diam., bears N.23*W., 6 lks. dist., marked $\frac{1}{4}$ S 33 B T (Old B.T.)

Thence

S.89*55'E., continuing my measurements

80.00 Set a granite stone, 18x9x6 ins., 12 ins. in the ground, for cor. of secs. 3 and 4; marked with 3 notches on E. and W. edges; from which

A hemlock, 14 ins. diam., bears S.65*30'E., 49 lks. dist., marked T 29 S R 2 W S 3 B T.

A hemlock, 8 ins. diam., bears S.17*30'W., 14 lks. dist., marked T 29 S R 2 W S 4 B T.