

6238  
36  
County Surveyor's Record, Douglas County, Oregon

Resurvey and Survey North Bdy., T. 29 S., R.2W.

CHAINS

Land, mountainous.  
Soil, light gravelly loam, 3rd rate.  
Timber, fir, hemlock and cedar.  
Undergrowth, rhododendron and young timber.

S.89\*55'E., resurveying N.bdy. of sec. 3.

Ascend SW. slope, through heavy timber and dense undergrowth.

- 5.00 Top of ridge, bears N. and S.; descend.  
13.85 Enter swampy ground, bears N. and S.  
15.85 Leave swampy ground, bears N. and S.  
18.45 Spring branch, course S.  
21.00 Creek, 4 lks. wide, course SE.; ascend.  
22.50 Top of spur, slopes SE.; descend.  
25.90 Enter swamp, bears N. and S.  
27.75 Leave swamp, bears N. and S.  
36.16 Intersect the cor. of secs. 33 and 34, which is a post, firmly set, marked and witnessed as described by the surveyor general. I perpetuate this cor., as follows:  
alongside the old cor.  
Set a granite stone, 18x10x6 ins., 12 ins. in the ground, for cor. of secs. 33 and 34, T. 28 S., R. 2 W. only, marked with 3 notches on E. and W. edges; from which  
A cedar, 30 ins. diam., bears N.55\*50'E., 49 lks. dist., marked T 28 S R 2 W S 34 B T. (Old B.T.)  
A hemlock, 20 ins. diam., bears N.1\*W., 31 lks. dist., marked T 28 S R 2 W S 33 B T (Old B.T.)  
Thence  
N.89\*53'E., continuing my measurements  
37.00 Creek, 3 lks. wide, course S.E.; along S. slope.  
40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{2}$  cor. of sec. 3 only, with brass cap marked

453  
1917

from which

A fir, 10 ins. diam., bears S.25\*E., 29 lks. dist.,