

County Surveyor's Record, Douglas County, Oregon.

Resurvey and Survey North Bdy., T. 29 S., R. 2 W.

CHAINS

only, which is a granite stone, firmly set, marked and witnessed as described by the surveyor general. I re-witness this cor., as follows: from cor.

A fir, 24 ins. diam., bears N.73\*45'E., 36 lks. dist., marked T 28 S R 2 W S 35 B T. (New B.T.)

A chinquapin, 8 ins. diam., bears N.49\*30'W., 33 lks. dist., marked T 28 S R 2 W S 34 B T (Old B.T.)

Thence

East, surveying N. bdy. of sec. 2, continuing my measurements.

37.70 Ravine, course NE.; ascend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  cor. of sec. 2 only, with brass cap marked

182  
1917

from which

A chinquapin, 16 ins. diam., bears S.59\*E., 25 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

A fir, 10 ins. diam., bears S.74\*W., 26 lks. dist., marked  $\frac{1}{4}$  S 2 B T.

48.80 Creek, 2 lks. wide, course N.; continue ascent.

61.00 Top of spur, slopes N.; descend.

68.30 Draw, course NE., continue descent.

76.38 Set a basalt stone, 20x8x5 ins., 15 ins. in the ground for  $\frac{1}{4}$  cor. of sec. 35, T. 28 S., R. 2 W. only, marked  $\frac{1}{4}$  on N. face; from which

A fir, 10 ins. diam., bears N.25\*15'E., 25 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

A pine, 12 ins. diam., bears N.36\*15'W., 43 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

78.50 Draw, course N.; ascend.

80.00 Set a basalt stone, 14 x 12 x 6<sup>in.</sup> 9 ins. in the ground for cor. of secs. 1 and 2, marked with 5 notches on W. and 1 notch on E. edge; from which

A hemlock, 12 ins. diam., bears S.35\*45'E., 35 lks. dist., marked T.29 S R 2 W S 1 B T.