

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

CHAINS	
40.86	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for $\frac{1}{4}$ cor., with brass cap marked.
	$\frac{\frac{1}{4} \text{ S25}}{\text{S36}}$ 1917
	from which
	A cedar, 20 ins. diam., bears N.81*E., 111 lks. dist., marked $\frac{1}{4}$ S 25 B T.
	A cedar, 12 ins., diam., bears S.73*E., 85 lks., dist., marked $\frac{1}{4}$ S 36 B T.
45.43	Top of spur, slopes SW.; descend.
60.05	Spring branch, course S.; ascend.
67.55	Top of spur, slopes S.; descend.
80.86	The cor. of secs. 25, 26, 35 and 36.
	Land, mountainous.
	Soil, rocky, 3rd rate.
	Timber, fir, pine, cedar and laurel.
	Undergrowth, maple, snowbrush and poison oak.
<hr/>	
	N.0*08'E., on a Sectional Guide Meridain, bet. secs. 25 and 26.
	Ascend through heavy timber and dense undergrowth.
23.10	Trail, bears E. and W.
24.30	Top of spur, slopes SW.; along W. slope.
29.95	Top of spur, slopes W.; descend.
37.33	Spring branch, course W.; along broken W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the
	ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{\frac{1}{4} \text{ S26}   \text{S25}}{1917}$
	from which
	A fir, 48 ins. diam., bears N.67*E., 54 lks. dist., marked $\frac{1}{4}$ S 25 B T.
	A fir, 48 ins. diam., bears N.40*30'W., 15 lks. dist., marked $\frac{1}{4}$ S 26 B T.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the