

6252
[Handwritten mark]

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 2 W.

| | |
|--------|---|
| CHAINS | <p>S.0*08'W., on a true line bet. secs. 1 and 2</p> <p>Ascend through heavy timber and dense undergrowth.</p> <p>35.00 Top of ridge, bears NW. and SE.; descend.</p> <p>35.95 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, mountainous.</p> <p>Soil, rocky, 3rd rate.</p> <p>Timber, fir, hemlock and pine.</p> <p>Undergrowth, rhododendron, chinquapin and young timber.</p> <hr/> <p>From the cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N.0*07'W., bet. secs. 34 and 35.</p> <p>Ascend through heavy timber and dense undergrowth.</p> <p>28.40 Top of spur ridge, bears NE. and W.; descend.</p> <p>34.00 Trail, bears NE. and SW.</p> <p>40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.</p> <div style="text-align: center;"> $\frac{1}{4}$ S34 S35 1917 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam. bears S.45*45'E., 43 lks. dist., marked $\frac{1}{4}$ S 35 B T.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S.88*15'W., 71 lks. dist., marked $\frac{1}{4}$ S 34 B T.</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 26, 27, 34 and 35, with brass cap marked</p> <div style="text-align: center;"> T29S R2W S27 S26 — — S34 S35 1917 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N.63*E. 78 lks. dist., marked T 29 S R 2 W S 26 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.34*E., 46 lks. dist., marked T 29 S R 2 W S 35 B T.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S.17*W., 61 lks. dist., marked T 29 S R 2 W S 34 B T.</p> |
|--------|---|